

## Technical Specifications

APC Back-UPS 500, 230V without auto shutdown software, ASEAN | BR500CI-AS | Downloaded on 10/18/2019 (EST)



## APC Back-UPS 500, 230V without auto shutdown software, ASEAN

BR500CI-AS

Call for More Information +65 6622 1639

- Battery Backup & Surge Protector for Electronics and Computers
- Includes: Qty 2 - Detachable 1.8 m IEC power cords, User Manual, Warranty card

### Output

Output power capacity	300Watts / 500VA
Max Configurable Power (Watts)	300Watts / 500VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz
Topology	Line Interactive
Waveform type	Stepped approximation to a sinewave
Output Connections	(3) IEC 320 C13 (Battery Backup)
Transfer Time	6ms typical : 10ms maximum

### Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Cord Length	1.83meters
Number of Power Cords	1

### Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	10hour(s)
Replacement Battery	<a href="#">APCRBC125</a> 
Expected Battery Life (years)	2 - 4

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Batteries & Runtime	
RBC Quantity	1
Battery Volt-Amp-Hour Capacity	73
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)

Communications & Management	
Audible Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering	
Surge energy rating	240Joules

Physical	
Maximum Height	185MM, 18.5CM
Maximum Width	115MM, 11.5CM
Maximum Depth	213MM, 21.3CM
Net Weight	4.9KG
Shipping weight	5.5KG
Shipping Height	257MM, 25.7CM
Shipping Width	190MM, 19.0CM
Shipping Depth	291MM, 29.1CM
Color	Black
Master Carton Units	1.0
Units per Pallet	60.0
SCC Codes	0073130426979 3

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC Back-UPS 500, 230V without auto shutdown software, ASEAN | BR500CI-AS | Downloaded on 10/18/2019 (EST)

Environmental	
Storage Elevation	0-15000meters

  

Conformance	
Standard warranty	2 years repair or replace

  

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOLI	Available in Documentation tab

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.