



Overview

Presentation	APC Smart-UPS SC is ideal for small and medium businesses looking to protect networking equipment and point-of-sale (POS) devices from power disturbances and outages. The Smart-UPS SC features network grade protection, hot swap batteries, and built-in data line protection for worry free uninterruptible power protection for increased availability. Built on the same standards as the award-winning Smart-UPS, Smart-UPS SC provides the basic features and manageability needed to protect entry-level applications
Lead time	Usually in Stock

General

Provided equipment	CD with software Smart UPS signalling RS-232 cable User manual
Product web sub-family	Entry level
Performance multiplier	1
Number of tare power	15 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	S
Value multiplier	1

Physical

Number of rack unit	0U
Colour	Grey
Depth	37.5 cm
Height	16.8 cm
Mounting location	Front

Mounting preference	No preference
Net weight	12.27 kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Width	11.9 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C14
Input voltage limits	195...265 V
Input voltage	230 V

Output

Rated power in W	390 W
Maximum configurable power in W	390 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	3 IEC 320 C13 1 IEC 320 C13 surge 2 IEC Jumpers
Curve equation	Efficiency
Curve fixed loss	0.0261
Curve load maximum	100 %
Curve load minimum	3 %
Curve proportional loss	0
Curve square loss	0.001
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	620 VA
Rated power in VA	620 VA
Transfer time	2 ms typical

Conformance

Product certifications	CE CE EAC GOST VDE VCCI
------------------------	--

Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	45 dBA
Heat dissipation	70 Btu/h
Show note OP temperature	No

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	5 h
Number of battery replacement quantity	1
Liquid value	0
Battery voltage	12 V
Battery capacity	12.0 Ah
Battery curve	Z
Battery charger power	26 W rated
Battery power in VAH	132 VAh runtime
Battery life	3...5 year(s)
Extended runtime	0

Communications & Management

Free slots	0
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	320 J
Noise suppression	Full time multi-pole noise filtering : 0.7% IEEE surge let-through : zero clamping response time : meets UL 1449
Data line protection	RJ45 modem/fax/DSL/10-100 base-T protection

Packing Units

Package 1 Weight	13.18 kg
Package 1 Height	31.8 cm
Package 1 width	26.2 cm
Package 1 Length	50.8 cm
Number of Units in Package 3	12

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------