

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Easy UPS On-Line SRV 6000VA RM 230V with Rail Kit

SRV6KRIRK

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	6000 W
Rated power in VA	6000 VA
Output connector type	Hard wire 3-wire (H N + E) 1
Number of rack unit	4U
Provided equipment	Basic UPS signalling RS-232 cable CD with software Rack mounting brackets Rack mounting support rails User manual USB cable

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

Colour	Black
Height	17.3 cm
Width	43.8 cm
Depth	71.0 cm
Net weight	61 kg

การสละสิทธิ์: เอกสารนี้ไม่มีวัตถุประสงค์เพื่อใช้แทน หรือใช้เพื่อกำหนดความเหมาะสม หรือความเข้ากันได้ของผลิตภัณฑ์อื่นสำหรับการใช้งานเฉพาะทาง

Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
USB compatible	Yes
Mounting position	Horizontal

Input

Input voltage limits	110...300 V half load 176...300 V full load
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Network frequency	40...70 Hz auto sensing

Output

Maximum configurable power in VA	6000 VA
Maximum configurable power in W	6000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	1 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	94 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

Conformance

Product certifications	CE EAC TISI
Standards	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...60 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...15000 m
Acoustic level	55 dBA
Heat dissipation	1172 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
--------------	-------------------

Battery voltage	192 V
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	7 h
Battery life	3...5 year(s)
Battery charger power	235 W rated

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	71 kg
Package 1 Height	123.19 cm
Package 1 width	60 cm
Package 1 Length	83.6 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------